

MIDDY MASTER FLASH®

**20
YEAR
WARRANTY**

5 Port Design for the Metal Roofing Industry One Design • Multiple Functions

ISO Quality, Price & Availability / TWO COMPOUNDS

ADVANCED OZONE RESISTANCE tested to...	EPDM 70 hour @ 500 pphm	SILICONE 70 hour @ 500 pphm
HIGH TEMPERATURE RESISTANCE Tested to		
Intermittent	+135°C (+275°F)	+260°C (+500°F)
Continuous	+100°C (+212°F)	+225°C (+437°F)
LOW TEMPERATURE RESISTANCE tested to...	- 55°C (-67°F)	-74°C (-101°F)
COMPRESSION SET minimum...	25%	50%

*Complete specification data and testing methods are available upon request.

One Design - Handling Many Jobs "2 Port Design" Multiple Functions

• Accommodates:

- ONE Pipe 0" - 2" - (0 - 50mm)
- ONE 3/8" (0.9525mm) pipe / cable
- 3-3/4" (9.52mm) Base

Weather Protection

Made of EPDM or Silicone, these flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.



Pipe Range	Compound	Part No.		Flashing Details	
Middy <ul style="list-style-type: none"> • One center port for 0" - 2" (0 - 50 mm) pipe/cable • One port up to 1/8 - 3/8" (0.9525 mm) pipe /cable 	Black EPDM	SQ081BA		A-Top Opening Diameter	Closed
	Grey EPDM	SQ081GA	B-Overall Height	2" (50mm)	
	Silicone	SQ082RA	C-Base Diameter	3-3/4" (9.52mm)	

To see our complete product line go to www.aztecwasher.com

