

MULTI-FLASH MASTER FLASH®

20
YEAR
WARRANTY

“TWO FLASHINGS IN ONE”

Multi-Flash is available in two compounds to handle virtually all job applications.

ISO Quality, Price & Availability / TWO COMPOUNDS / 10 SIZES

	EPDM	SILICONE
ADVANCED OZONE RESISTANCE tested to...	70 hour @ 500 pphm	70 hour @ 500 pphm
HIGH TEMPERATURE RESISTANCE		
Tested to Intermittent	+135°C (+275°F)	+260°C (+500°F)
Continuous	+100°C (+212°F)	+225°C (+437°F)
LOW TEMPERATURE RESISTANCE tested to...	-55°C (-67°F)	-74°C (-101°F)
COMPRESSION SET minimum...	25%	50%

*Complete specification data and testing methods are available upon request.

Weather protection

Made of EPDM or Silicone, these flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.

A “C12” ASTM

Additional requirement was added to assure conformance to the most stringent ozone/weathering specifications available.

Base flexibility

The base is designed to form a seal on most panel configurations and roof pitch regardless of pipe location.

Easy on site customizing

Smooth cut is intended to eliminate use of razor blades. Stainless steel gripper to secure a retro custom fit. **(GRIPPER INCLUDED)**












MULTI-FLASH MASTER FLASH®

**20
YEAR
WARRANTY**

SIZING CHART

Check diameter of pipe. Select the appropriate Multi-Flash Master Flash® for pipe or duct diameter. Only use maximum pipe diameters on minimal roof angles. For extreme pitch or surface irregularity select next larger size. Then refer to the part number for the Multi-Flash Master Flash® desired.

	Pipe Size		Compound	Part No.		Flashing Details	
#2	STANDARD 7/8" - 4" (22 - 101.6 mm)	RETROFIT N/A	Black EPDM	MF201BA		A-Top opening diameter	Closed
			Silicone	MF202RA		B-Overall height	0" (0 mm)
#3	STANDARD 1/4" - 5-3/4" (6.4 - 146 mm)	RETROFIT 2" - 4-1/2" (50.8 - 114.3 mm)	Black EPDM	MF301BA		A-Top opening diameter	Closed
			Silicone	MF302RA		B-Overall height	0" (0 mm)
#4	STANDARD 2-3/4" - 7" (70 - 177.8 mm)	RETROFIT N/A	Black EPDM	MF401BA		A-Top opening diameter	2-3/4" (70 mm)
			Silicone	MF402RA		B-Overall height	0" (0 mm)
#5	STANDARD 4" - 8-1/4" (101.6 - 209.5 mm)	RETROFIT 3-1/2" - 6-3/4" (88.9 - 171.4 mm)	Black EPDM	MF501BA		A-Top opening diameter	4" (101.6 mm)
			Silicone	MF502RA		B-Overall height	0" (0 mm)
#6	STANDARD 4-3/4" - 10" (121 - 254 mm)	RETROFIT N/A	Black EPDM	MF601BA		A-Top opening diameter	4-3/4" (121 mm)
			Silicone	MF602RA		B-Overall height	0" (0 mm)
#7	STANDARD 5-1/2" - 11-1/2" (140 - 292 mm)	RETROFIT 0" - 0"	Black EPDM	MF701BA		A-Top opening diameter	5-1/2" (140 mm)
			Silicone	MF702RA		B-Overall height	0" (0 mm)
#8	STANDARD 6-3/4" - 13-1/2" (171.4 - 343 mm)	RETROFIT 6-1/2" - 12" (165.1 - 304.8 mm)	Black EPDM	MF801BA		A-Top opening diameter	6-3/4" (171.4 mm)
			Silicone	MF802RA		B-Overall height	0" (0 mm)
#9	STANDARD 9-1/2" - 20-1/2" (241 - 520 mm)	RETROFIT N/A	Black EPDM	MF901BA		A-Top opening diameter	9-1/2" (241 mm)
			Silicone	MF902RA		B-Overall height	0" (0 mm)
Maxi	STANDARD 12" - 28-1/2" (305 - 724 mm)	RETROFIT 13" - 27" (330.2 - 685 mm)	Black EPDM	MF951BA		A-Top opening diameter	12" (304 mm)
			Silicone	MF9502RA		B-Overall height	0" (0 mm)
						C-Base dimensions	34" (863.6 mm)

To see our complete product line go to www.aztecwasher.com



13821 Danielson Street, Poway, CA 92064 • 1-800-WASHER 5 (927-4375) • Ph: 858-513-4350 • Fax: 858-513-4305