

STANDARD MINI MASTER FLASH®



Specifically Designed For Solar & Electrical Applications

ISO Quality, Price & Availability / TWO COMPOUNDS

ADVANCED OZONE RESISTANCE tested to...	EPDM 70 hour @ 500 pphm	SILICONE 70 hour @ 500 pphm
HIGH TEMPERATURE RESISTANCE Tested to		
Intermittent	+135°C (+275°F)	+260°C (+500°F)
Continuous	+100°C (+212°F)	+225°C (+437°F)
LOW TEMPERATURE RESISTANCE tested to...	- 55°C (-67°F)	-74°C (-101°F)
COMPRESSION SET minimum...	25%	50%

*Complete specification data and testing methods are available upon request.

Smallest flashing available

- 1/16" (1.6mm) pipe / cable
- 3/4" (19.0mm) overall height
- 2-1/4" (57.2mm) Base
- Nine color options available
- Specifically designed for solar & electrical applications



Pipe Range	Compound	Part No.	Flashing Details
B-Overall Height	3/4" (19.0mm)		
C-Base Diameter	2 - 1/4" (57.2mm)		

Mini

Pipe Range

Compound

Part No.

Flashing Details

(1/8" - 3/4")
3.2mm - 19.1 mm

Black EPDM


SQ101BA

Grey EPDM

SQ101GA

Silicone

SQ102RA



A-Top Opening Diameter	1/16" (1.6mm)
B-Overall Height	3/4" (19.0mm)
C-Base Diameter	2 - 1/4" (57.2mm)

To see our complete product line go to www.aztecwasher.com

