



Master Flash® Metal Roof Sealing Tape

Sealing Joints, Seams, Holes and More!

Use on:

EPDM, TPO, Hypalon, Aged PVC, Modifies, and all metals.

Technical Data	
Adhesion	20lbs+/in width
Application Temperature	150°F to -20°F ambient
Elongation	>700% +/- 100
Low Temperature Flexibility	1/2" radius at -30°F
Permanence	.001 perms maximum
Pliability	No cracks in membrane
Temperature Flexibility Range	-70°F - >200°F
Tensile Break	PSI: 4500 PSI +/- 500 PSI
Water Proof Test (ASTME 96B)	.005 grms/100" sq./24hrs/100°F



Master Flash® Metal Roof Sealing Tape

For use on virtually all metal roofs, Master Flash® Roof Sealing Tape features a UV stable backing that is available in Black, Gray, Tan and White. With the exception of surface prep, Master Flash® Roof Sealing Tape is a one-step permanent repair system for virtually all roof types, and roof accessories.

Master Flash® Metal Roof Sealing Tape

creates a waterproof, moisture, and air tight barrier with no additional sealing required. Master Flash® Roof Sealing Tape remains flexible to temperatures as low as -70°F making it virtually impossible to thermally shock the seam causing a leak.

Master Flash® Metal Roof Sealing Tape

is pressure activated, permanently bonding to virtually any metal roof type. Works great for repairing metal flashings, venting, gutters, skylights, copings, ductwork and more.

UV Stable Backing Available in:
Black, Grey, White and Tan

The enhanced sealing solutions
100% solids formulation of synthetic resins, thermoplastics and non-curing rubber (non butyl with a built in primer)

Available In:
2", 4", 6" & 9" Widths
50ft lengths

Total thickness
34 mils (+/- 2 mils)



MRTR101-ST

*Heavy Duty Steel Roller NOT Included

***NOTE:**

Master Flash® Roof Sealing Tape does not stick to silicone.

