



Universal Mini Master Flash®

**Specifically Designed For
Solar & Electrical Applications**

Advanced Ozone Resistance tested to...		EPDM 70 hour @ 500 pphm	HIGH TEMP RED/GRAY SILICONE 70 hour @ 500 pphm
High Temperature Resistance Tested to	Intermittent	+135°C (+275°F)	+260°C (+500°F)
	Continuous	+100°C (+212°F)	+225°C (+437°F)
Low Temperature Resistance tested to...		- 55°C (-67°F)	- 74°C (-101°F)
Compression Set Maximum...		25%	50%

*Complete specification data and testing methods are available upon request.

**Pipe Range: Closed-1" (0-25mm)
Overall Height: 3/4" (19mm) • Base: 2-1/4" (57mm)**

Available in fourteen EPDM colors

Unique compression seal technology

Single port for cables or wires to accommodate copper pipe and electrical cabling


Weather Protection
Made of EPDM or High Temp Silicone,
These flashings are compounded specifically for maximum resistance to weathering due to ozone and ultraviolet light.

Sleeve flexibility absorbs vibration and pipe movement caused by expansion/contraction

Adaptable Base

The base is designed to mold to most panel configurations and roof pitches regardless of pipe location.

Easy on-site customization accommodates all normal installations.



Mini Universal Flashing Details

A-Top Opening	Closed
B-Overall Height	1-1/2" (38mm)
C-Base	4" (101mm)



Master Flash® was used to create a new engineering standard for profiled roofing by the International Association of Plumbing and Mechanical Officials (for the Uniform Plumbing Code) and remains the only product listed. These products are also listed for use with Type B vents.

The addition of fire retarding agents milled directly into the rubber compound created a self extinguishing feature which enables it to be used with type "B" vents. Listed with IAPMO certification No. 3121

